

# MastaBond

## MASONRY ADHESIVE



## TECH DATA

**MastaBond** is a yellow plaster based cement for adhering plasterboard to masonry surfaces. It has a consistent working time of 30 minutes with a 50 minute setting time. Its unique gritty texture delivers fast and secure bond allowing for quick and easy installation.



### Performance

#### Mixing

Mixes easily by hand or electric mixer.

#### Colour

Yellow for easy identification.

#### Body and Grab

Good body for easy placement of daubs and great initial grab. The gritty texture enables easy levelling of plasterboard to masonry surface and extra adhesion.

#### Sustainable

Low VOC meeting sustainable building project requirements.

### Benefits

- Excellent grab
- Easy to mix
- Easy to apply

### Product Information

SIZE	20kg paper bag		
TYPE	Setting powder cement		
MIXING RATIO	1L of water to 2kg of MastaBond		
WORKING TIME	30 – 50 minutes		
SETTING TIME	50 minutes		
SYSTEM USAGE	<input checked="" type="checkbox"/> Masonry walls	<input checked="" type="checkbox"/> Jointing	<input checked="" type="checkbox"/> Back-blocking
	<input checked="" type="checkbox"/> Cornice	<input checked="" type="checkbox"/> Wet area systems	<input checked="" type="checkbox"/> Fire rated systems
VOC	<50g/L as VOC content per coating		

# MastaBond

## MASONRY ADHESIVE



## TECH DATA

### Application

- Use MastaBond only for masonry adhesion applications.
- MastaBond should not be used on autoclaved aerated concrete (AAC), multi layer systems, walls over 3m high and walls that could get wet during service. It also cannot be used where the masonry substrate is more than 25mm out of plane.
- Walls must be dry and paint free, clean from oil, dust, efflorescence, release agents or any other material that could impair the bonding of MastaBond.
- Always use clean tools and containers.
- Pour the required amount of clean tap water into a container. Add the powder into water, mixing continuously to a smooth, thick consistency. Soaking is not recommended.
- Only mix enough cement to be used in 30 minutes and do not contaminate with previously mixed batches. Once the material starts to set it cannot be remixed.

### Optimise product performance by:

- Storing in a dry, well ventilated environment fully protected from the weather.
- Washing tools before product dries and hardens.
- Ensuring MastaBond does not dry out before setting has taken place under severe hot dry conditions.



Quality  
ISO 9001

SAI GLOBAL

Knauf products manufactured in Australia are produced in accordance with quality systems certified as complying with AS/NZS ISO 9001:2008.

### Warranty

Knauf's products are guaranteed by a 10 Year Warranty. Visit [knaufplasterboard.com.au](http://knaufplasterboard.com.au) for details.

### Technical Advice

For technical advice, please call Knauf technical services on **1300 724 505**.