

MastaFinish

FINISHING COMPOUND



TECH DATA

MastaFinish is a premium premixed air drying compound designed for the finishing coat over plasterboard joints. It is suitable for use over MastaBase and MastaLongset Bedding Cements and is ready to use from the bucket, with no need to add water when hand trowelling. MastaFinish is the solution for topping plasterboard joints when a superior finish is desired for any commercial or residential project.



Performance

Body

Great body for hand trowelling, delivering smooth and effortless final coating for joints, internal and external angles and fastener heads. Maintains body when mixed or worked on the hawk.

Drying

Does not dry out too fast, allowing time to produce fine, feathered edges. Very resistant to cracking in internal angles.

Colour

A dark brown colour when applied making it easy to determine progress of jointing. The change in colour as MastaFinish dries indicates that joints are dry and ready for sanding. The dark colour is also useful for identifying patches to be sanded after minor repairs to walls have been completed.

Sanding

Use electric sanders or sand by hand to create a scratch and swirl free finish.

Sustainable

Low VOC meeting sustainable building project requirements.

Benefits

- > Superior finish
- > Easy to trowel
- > Easy to sand

Product Information

SIZE	20kg bucket
TYPE	Heavy weight air drying premixed paste
DRYING TIME	24 hours under normal drying conditions
SYSTEM USAGE	<input checked="" type="checkbox"/> Final coat
	<input checked="" type="checkbox"/> Standard <input checked="" type="checkbox"/> Fire rated
VOC	<50g/L as VOC content per coating
SPECIFIC DENSITY	1.6g/cc

MastaFinish

FINISHING COMPOUND



TECH DATA

Application

- MastaFinish is ready to use for hand trowelling. For mechanical tools, if necessary add clean tap water in small amounts and mix until desired consistency is achieved.
- Excessive thinning may cause cracking or increased shrinkage. Do not mix with any other material.
- Maintain a minimum 10°C working temperature during application and drying.
- Sand lightly by hand using 150 grit paper or 180 sanding mesh. When using an electric sander use 220 grit paper.
- MastaFinish will accept most types of decorative finishes. In accordance with AS/NZS 2311 *Guide to the painting of buildings*, a three coat paint system must be used. This consists of a sealer/undercoat and two coats of paint.

Optimise product performance by:

- Firmly closing the lid to prevent the compound from drying out.
- Washing tools before product dries and hardens.
- Storing in a dry, well ventilated environment fully protected from the weather.



Quality
ISO 9001

SAIGLOBAL

Knauf products manufactured in Australia are produced in accordance with quality systems certified as complying with AS/NZS ISO 9001:2008.

Warranty

Knauf's products are guaranteed by a 10 Year Warranty. Visit knaufplasterboard.com.au for details.

Technical Advice

For technical advice, please call Knauf technical services on **1300 724 505**.