

# Uniflott

## JOINTING COMPOUND



## TECH DATA

**Uniflott** is a plaster based cement specifically developed for filling joints of Stratopanel systems. Uniflott is a setting cement providing a strong, highly crack resistant joint for Stratopanel. It has a consistent working time of 45 minutes with a 60 minute setting time.

Mastalite is recommended for finishing Stratopanel joints after applying Uniflott for easy sanding and smooth finish.



### Performance

#### Mixing

Wets out quickly and mixes easily to a smooth, creamy consistency.

#### Easy Application

Easy application due to its creamy pliable consistency.

#### Low Shrinkage

Less re-filling required due to its low shrinkage properties

#### Strength

Fast strength development providing a hard, highly crack resistant joint.

### Benefits

- > Low shrinkage
- > High joint strength

### Product Information

SIZE	5 kg paper bag
TYPE	Plaster based jointing compound
MIXING RATIO	2.4 L of water to 5 kg of Uniflott
WORKING TIME	45 minutes
SETTING TIME	60 minutes
SYSTEM USAGE	<input checked="" type="checkbox"/> Stratopanel

# Uniflott

## JOINTING COMPOUND

# KNAUF

## TECH DATA

### Application

- Clean dust from joints after fixing the boards. Use a wet brush.
- Prime site cut edges of gf Stratopanel before jointing with Knauf Penetrating Primer.
- Pour the required amount of clean tap water into a container. Add the powder into water, mixing continuously to a thick, creamy consistency. Soaking is not recommended.
- Only mix enough jointing compound to be used in 45 minutes and do not contaminate with previously mixed batches. Once the material starts to set it cannot be remixed.
- Fill joints fully with Uniflott using Knauf Pouch Gun.
- Scrape off excess Uniflott after compound is completely dry.
- Sand after complete drying.
- Use Mastalite for finishing joints and screw heads.
- Always use clean tools and containers.
- Must not be applied over air drying compounds.
- Do not fill joints at temperatures below 10° C.

### Optimise product performance by:

- Storing in a dry, well ventilated environment fully protected from the weather.
- Washing tools before product dries and hardens.
- Ensuring Uniflott does not dry out before setting has taken place under severe hot dry conditions.



### Warranty

Knauf's products are guaranteed by a 10 Year Warranty.

For details visit

[knaufplasterboard.com.au](http://knaufplasterboard.com.au)

### Technical Advice

AU 1300 724 505.