

Box Ready MastalLine

All Purpose Jointing Compound



PRODUCT DATA SHEET

Key Benefits

- › Formulated for use with automatic tools
- › Premixed for easy use and speed
- › No additional mixing required



Box Ready MastalLine is a thinned down premixed all purpose compound that can be applied with automatic tools immediately from the bucket - no mixing required. It can be used interchangeably with standard MastalLine whenever automatic tools such as a box or taping tool are used.

Box Ready MastalLine can be used with the appropriate automatic tool for 1st, 2nd and 3rd coats, internal and external corners, and screw heads. Refer to the [Knauf Plasterboard Installation Guide](#) for jointing and finishing requirements.

Product Information

PRODUCT SIZE	20 kg in a 15 litre bucket
TYPE	Mid weight air drying premixed all purpose compound
DRYING TIME	Allow 24 hours. Drying time will depend on the weather.
SYSTEM USAGE	✓ Bedding ✓ Second coat ✓ Final coat
VOC	<50 g/L
DENSITY	1.35 g/cc

Box Ready MastalLine

All Purpose Jointing Compound



PRODUCT DATA SHEET

Performance

Body

Thinned down ready to use through mechanical tools.

Drying

Convenient drying time to obtain thin edges when feathering as it does not dry out too fast.

Colour

Light colour when applied, drying to a white finish

Sanding

Can be sanded by hand or by electric sanders. Leaves a professional finish

Safe to Use

Low VOC and non-hazardous (according to Safe Work Australia criteria).



Application

- > Box Ready MastalLine is ready to use through mechanical tools. No need to dilute.
- > Prime the loading pump with the compound and then fill the box or automatic taping tool.
- > Apply the compound to the wall using appropriate setting method (box, taping tool, corner tool, etc). Ensure sufficient compound under paper tape for maximum adhesion.
- > As with all compounds, excessive thinning may cause cracking or increased shrinkage. Do not mix with any other material.
- > Ensure adequate ventilation for optimum drying time.
- > When using Box Ready MastalLine for all three coats, joints must be back-blocked. MastaMate Paper Tape is recommended for use with Box Ready MastalLine.
- > For a stronger joint, use MastaMate Paper Tape and MastaBase/Longset or

MastaTape Universal for the first two coats, with Box Ready MastalLine as the final coat.

- > Allow Box Ready MastalLine to dry completely between coats. We recommend 24 hours. Drying time will depend on the weather.
 - > Sand lightly by hand using 180 grit paper or 220 sanding mesh. When using an electric sander use 220 grit paper.
 - > Box Ready MastalLine will accept most types of decorative finishes. In accordance with AS/NZS 2311 Guide to the painting of buildings, a three coat paint system must be used. This consists of a sealer/undercoat and two coats of paint.
- Optimise product performance by:**
- > Closing the lid to prevent the compound from drying out.
 - > Washing tools before product dries and hardens.
 - > Storing in a dry, well ventilated environment fully protected from the weather.

Warranty

Knauf's products are guaranteed by a 10 Year Warranty.

For details visit

www.knauf.solutions

Technical Advice

AU 1300 724 505